

View Online at <https://aerobasegroup.com/nsn/5950-00-489-2099>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.190 inches single mounting facility single center group2.190 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.750 inches single mounting facility single center group1.750 inches single mounting facility single center group

Frequency Rating:

45.0 hertz single component and 45.0 hertz single component and 440.0 hertz single component440.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Body Length:

2.810 inches 2.810 inches

Body Width:

2.380 inches 2.380 inches

Body Height:

2.880 inches 2.880 inches

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 3 secondary single component3 secondary single component

Thread Size:

0.138 inches single group0.138 inches single group

Winding Operating Current:

2.7 amperes dc single component 1st secondary

Winding Operating Voltage:

8.50 dc volts single component 1st secondary

Special Features:

All secondary voltage and current has been rectified

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

13 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0