

View Online at <https://aerobasegroup.com/nsn/5950-00-489-6996>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.875 inches single mounting facility single center group

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Wye-wye

Body Length:

3.690 inches

Body Width:

2.630 inches

Body Height:

2.630 inches

Maximum Operating Temp:

95.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

8.0 milliamperes ac single component single primary

Winding Operating Voltage:

8.80 ac volts single component 1st secondary24.50 ac volts single component 2nd secondary115.00 ac volts single component single primary5.50 ac volts single component 4th secondary15.20 ac volts single component 3rd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

16 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0