NSN 5950-00-489-6997

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-489-6997

Not established Overal Length: 4.095 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.750 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.875 inches single mounting facility single center group Frequency Rating: 380.0 heft single component and 420.0 heft single component Input-output Phase Relationship: Three phase to single phase single component Body Length: 3.720 inches Body Width: 2.630 inches Body Height: 2.630 inche	
4.995 indees Center To Center Distance Between Mounting Facilities Parallel To Length: 2.750 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.875 inches single mounting facility single center group Frequency Rating: 380.0 hertz single component and 420.0 hertz single component Input-output Phase Relationship: Three phase to single phase single component Body Length: 3.720 inches Body Udth: 2.630 inches Body Height: 2.630 inches Body Height: 2.630 inches Mounting Facility Quantity: 4 single group Mounting Method: Thready he is gingle component and 4 secondary single component Intraduction And Quantity: 1 primary single component and 4 secondary single component Thready Uty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group Chingl Operating Current: 5.00 milliamperes ac single component 4th secondary	
2.750 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.875 inches single mounting facility single center group Frequency Rating: 380.0 hertz single component and 420.0 hertz single component Input-output Phase Relationship: Three phase to single phase single component Body Length: 3.720 inches Body Width: 2.630 inches Body Height: 2.630 inches Body Height: 2.630 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 4 secondary single component Thready Qty Per Inch (pi): 32 single group Thread Size: 0.164 inches single group Winding Operating Current: 50.0 milliamperes ac single component 4th secondary	
2.750 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.875 inches single mounting facility single center group Frequency Rating: 380.0 hertz single component and 420.0 hertz single component Input-output Phase Relationship: Three phase to single phase single component Body Length: 3.720 inches Body Width: 2.630 inches Body Height: 2.630 inches Body Height: 2.630 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 4 secondary single component Thready Qty Per Inch (pi): 32 single group Diread Size: 0.164 inches single group Winding Operating Current: 50.0 milliamperes ac single component 4th secondary	
Center To Center Distance Between Mounting Facilities Parallel To Width: 1.875 inches single mounting facility single center group Frequency Rating: 380.0 hertz single component and 420.0 hertz single component Input-output Phase Relationship: Three phase to single phase single component Body Length: 3.720 inches Body Width: 2.630 inches Body Height: 2.630 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 4 secondary single component Thready Qty Per Inch (tpi): 32 single group Muta Size: 0.164 inches single group Winding Operating Current: 50.0 milliamperes ac single component 4th secondary	
1.875 inches single mounting facility single center group Frequency Rating: 380.0 hertz single component and 420.0 hertz single component Input-output Phase Relationship: Three phase to single phase single component Body Length: 3.720 inches Body Width: 2.630 inches Body Height: 2.630 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 4 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group Winding Operating Current: 50.0 milliamperes ac single component 4th secondary	
Frequency Rating: 380.0 hertz single component and 420.0 hertz single component Input-output Phase Relationship: Three phase to single phase single component Body Length: 3.720 inches Body Width: 2.630 inches Body Height: 2.630 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Facility Quantity: 1 primary single component and 4 secondary single component Thready Oty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group Winding Operating Current: 50.0 milliamperes ac single component 4th secondary	
Input-output Phase Relationship: Three phase to single phase single component Body Length: 3.720 inches Body Width: 2.630 inches Body Height: 2.630 inches Body Height: 2.630 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 4 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group Winding Operating Current: 50.0 milliamperes ac single component 4th secondary	
Three phase to single phase single component Body Length: 3.720 inches Body Width: 2.630 inches Body Height: 2.630 inches Body Height: 2.630 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 4 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group Studing Operating Current: 50.0 milliamperes ac single component 4th secondary	
Body Length: 3.720 inches Body Width: 2.630 inches Body Height: 2.630 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 4 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group Winding Operating Current: 50.0 milliamperes ac single component 4th secondary	
3.720 inches Body Width: 2.630 inches Body Height: 2.630 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 4 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group Winding Operating Current: 50.0 milliamperes ac single component 4th secondary	
Body Width:2.630 inchesBody Height:2.630 inchesBody Height:2.630 inchesInclosure Type:Hermetically sealedMounting Facility Quantity:4 single groupMounting Method:Threaded hole single groupWinding Function And Quantity:1 primary single component and 4 secondary single componentThready Qty Per Inch (tpi):32 single groupThread Size:0.164 inches single groupWinding Operating Current:50.0 milliamperes ac single component 4th secondary	
2.630 inches Body Height: 2.630 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 4 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group Winding Operating Current: 50.0 milliamperes ac single component 4th secondary	
Body Height:2.630 inchesInclosure Type:Hermetically sealedMounting Facility Quantity:4 single groupMounting Method:Threaded hole single groupWinding Function And Quantity:1 primary single component and 4 secondary single componentThready Qty Per Inch (tpi):32 single groupThread Size:0.164 inches single groupWinding Operating Current:5.0 milliamperes ac single component 4th secondary	
2.630 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 4 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group Winding Operating Current: 5.0. milliamperes ac single component 4th secondary	
Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 4 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group Winding Operating Current: 5.0 milliamperes ac single component 4th secondary	
Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 4 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group Winding Operating Current: 5.00 milliamperes ac single component 4th secondary	
Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 4 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group Winding Operating Current: 50.0 milliamperes ac single component 4th secondary	
4 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 4 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group Winding Operating Current: 50.0 milliamperes ac single component 4th secondary	
Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 4 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group Winding Operating Current: 50.0 milliamperes ac single component 4th secondary	
Threaded hole single group Winding Function And Quantity: 1 primary single component and 4 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group Winding Operating Current: 50.0 milliamperes ac single component 4th secondary	
Winding Function And Quantity: 1 primary single component and 4 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group Winding Operating Current: 50.0 milliamperes ac single component 4th secondary	
1 primary single component and 4 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group Winding Operating Current: 50.0 milliamperes ac single component 4th secondary	
Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group Winding Operating Current: 50.0 milliamperes ac single component 4th secondary	
32 single group Thread Size: 0.164 inches single group Winding Operating Current: 50.0 milliamperes ac single component 4th secondary	
Thread Size: 0.164 inches single group Winding Operating Current: 50.0 milliamperes ac single component 4th secondary	
0.164 inches single group Winding Operating Current: 50.0 milliamperes ac single component 4th secondary	
Winding Operating Current: 50.0 milliamperes ac single component 4th secondary	
50.0 milliamperes ac single component 4th secondary	
Winding Operating Voltage	
Winding Operating Voltage:	
8.10 ac volts single component 3rd secondary115.00 ac volts single component single primary8.10 ac volts sin	gle component 4th
secondary	
Thread Series Designator:	
Unc single group	
Terminal Type And Quantity:	
14 turret	
Shelf Life:	
N/a	

NSN 5950-00-489-6997

Power Transformer - Page 2 of 2

Demilitarization:

No

Fiig:

A058b0

