

View Online at <https://aerobasegroup.com/nsn/5950-00-491-4395>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.938 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.817 inches single mounting facility single center group

**Frequency Rating:**

400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield brought out to terminal single component

**Body Length:**

3.156 inches

**Body Width:**

2.844 inches

**Body Height:**

2.750 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded hole single group

**Winding Function And Quantity:**

1 primary single component and 2 secondary single component

**Thread Qty Per Inch (tpi):**

32 single group

**Thread Size:**

0.164 inches single group

**Winding Operating Current:**

3.3 amperes ac single component 2nd secondary

**Winding Operating Voltage:**

58.00 ac volts single component 1st secondary 17.60 ac volts single component 2nd secondary 5.00 ac volts single component single primary and 100.00 ac volts single component single primary and 110.00 ac volts single component single primary and 120.00 ac volts single component single primary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

11 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0