

View Online at <https://aerobasegroup.com/nsn/5950-00-492-2669>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.500 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

2.000 inches

Body Width:

2.000 inches

Body Height:

1.688 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

300.0 milliamperes ac single component 1st secondary

Winding Power Rating:

6.0 volts-amperes single component 1st secondary52.0 volts-amperes single component single primary54.0 volts-amperes single component 2nd secondary

Winding Operating Voltage:

26.00 ac volts single component single primary and 22.00 ac volts single component 2nd secondary and 20.00 ac volts single component 1st secondary115.00 ac volts single component single primary32.00 ac volts single component 2nd secondary and 54.00 ac volts single component 2nd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

11 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0