

View Online at <https://aerobasegroup.com/nsn/5950-00-493-9395>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.427 inches single mounting facility single center group and 2.447 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.740 inches single mounting facility single center group and 1.760 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Wye-delta

Body Length:

2.960 inches

Body Width:

2.570 inches

Body Height:

1.850 inches

Maximum Operating Temp:

170.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

2.0 amperes dc single component all secondary

Winding Power Rating:

36.8 volts-amperes single component 2nd secondary 21.0 volts-amperes single component 1st secondary

Winding Operating Voltage:

18.40 dc volts single component 2nd secondary 10.50 dc volts single component 1st secondary

Test Data Document:

96214-636244 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

13 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0