

View Online at <https://aerobasegroup.com/nsn/5950-00-493-9397>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.250 inches single mounting facility single center group3.250 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.000 inches single mounting facility single center group2.000 inches single mounting facility single center group

**Frequency Rating:**

400.0 hertz single component400.0 hertz single component

**Input-output Phase Relationship:**

Three phase to three phase single componentthree phase to three phase single component

**Transformer Winding Connection Type:**

Delta-wyedelta-wye

**Body Length:**

3.870 inches 3.870 inches

**Body Width:**

3.020 inches 3.020 inches

**Body Height:**

2.570 inches 2.570 inches

**Inclosure Type:**

Fully enclosedfully enclosed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded hole single groupthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 5 secondary single component5 secondary single component

**Thread Size:**

0.138 inches single group0.138 inches single group

**Winding Operating Current:**

500.0 milliamperes ac single component 2nd secondary

**Winding Power Rating:**

5.25 volts-amperes single component 2nd secondary88.0 volts-amperes single component 4th secondary64.5 volts-amperes single component 3rd secondary

**Winding Operating Voltage:**

9.84 ac volts single component 1st secondary21.50 ac volts single component 3rd secondary10.50 ac volts single component 2nd secondary

**Special Features:**

One primary winding; five secondary windings

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

19 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0