

View Online at <https://aerobasegroup.com/nsn/5950-00-493-9397>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.250 inches single mounting facility single center group3.250 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group2.000 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single componentthree phase to three phase single component

Transformer Winding Connection Type:

Delta-wyedelta-wye

Body Length:

3.870 inches 3.870 inches

Body Width:

3.020 inches 3.020 inches

Body Height:

2.570 inches 2.570 inches

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded hole single groupthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 5 secondary single component5 secondary single component

Thread Size:

0.138 inches single group0.138 inches single group

Winding Operating Current:

500.0 milliamperes ac single component 2nd secondary

Winding Power Rating:

5.25 volts-amperes single component 2nd secondary88.0 volts-amperes single component 4th secondary64.5 volts-amperes single component 3rd secondary

Winding Operating Voltage:

9.84 ac volts single component 1st secondary21.50 ac volts single component 3rd secondary10.50 ac volts single component 2nd secondary

Special Features:

One primary winding; five secondary windings

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

19 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0