NSN 5950-00-493-9398

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-493-9398

_					-		-		
R	ام	iэ	hi	liŧ۱	, II	nd	ira	tor:	
ı	σı	ıa	NI.	116		ıи	ıva	w.	

Not established

Hazardous Locations/environmental Protection:

Moisture resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.302 inches single mounting facility single center group and 3.322 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.865 inches single mounting facility single center group and 2.885 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Wye-delta

Body Length:

3.970 inches

Body Width:

3.660 inches

Body Height:

1.750 inches

Maximum Operating Temp:

170.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

4.4 amperes dc single component single secondary

Winding Operating Voltage:

58.00 dc volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 tab, solder lug

Shelf Life:

N/a

NSN 5950-00-493-9398

Power Transformer - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0