## NSN 5950-00-494-0570

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-494-0570

| Reliability Indicator:   |
|--|
| Not established  |
| Center To Center Distance Between Mounting Facilities Parallel To Length:                  |
| 5.000 inches single mounting facility single center group                                  |
| Center To Center Distance Between Mounting Facilities Parallel To Width:                   |
| 3.000 inches single mounting facility single center group                                  |
| Frequency Rating:  |
| 50.0 hertz single component or 60.0 hertz single component                                 |
| Input-output Phase Relationship:   |
| Single phase to single phase single component  |
| Body Length:   |
| 6.000 inches   |
| Body Width:  |
| 4.000 inches   |
| Body Height:   |
| 4.750 inches   |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Facility Quantity:  |
| 4 single group   |
| Mounting Method:   |
| Threaded hole single group   |
| Winding Function And Quantity:   |
| 1 primary single component and 3 secondary single component                                |
| Thready Qty Per Inch (tpi):  |
| 20 single group  |
| Thread Size:   |
| 0.250 inches single group  |
| Winding Operating Current:   |
| 50.0 milliamperes ac single component 3rd secondary  |
| Winding Operating Voltage:   |
| 60.00 ac volts single component 3rd secondary60.00 ac volts single component 2nd secondary |
| Thread Series Designator:  |
| Unc single group   |
| Terminal Type And Quantity:  |
| 12 tab, solder lug   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
|  |

## NSN 5950-00-494-0570

Power Transformer - Page 2 of 2

**Fiig:** A058b0

