

View Online at <https://aerobasegroup.com/nsn/5950-00-496-3515>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.440 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.560 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Wye-delta

Maximum Transformer Power Rating:

717.9 volt-ampere single component

Body Length:

4.100 inches

Body Width:

3.500 inches

Body Height:

2.150 inches

Maximum Operating Temp:

155.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

3.5 amperes dc single component 3rd secondary

Winding Power Rating:

214.1 volts-amperes single component 2nd secondary 84.8 volts-amperes single component 3rd secondary 204.9 volts-amperes single component 4th secondary

Winding Operating Voltage:

27.50 dc volts single component 2nd secondary 14.00 dc volts single component 3rd secondary 10.30 dc volts single component 4th secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

16 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0