## NSN 5950-00-496-6835

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-496-6835
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.125 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.625 inches single mounting facility single center group
Frequency Rating:
55.0 hertz single component and 65.0 hertz single component
Input-output Phase Relationship:
Three phase to three phase single component
Winding Shielding Method:
Internal shield brought out to terminal single component
Body Length:
3.562 inches
Body Width:
3.062 inches
Body Height:
4.875 inches
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Thready Qty Per Inch (tpi):
32 single group
Thread Size:
0.138 inches single group
Winding Operating Current:
900.0 milliamperes ac single component single secondary
Winding Operating Voltage:
86.70 ac volts single component single secondary203.00 ac volts single component single primary
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
7 solder stud
Shelf Life:
N/a

**Unit Of Measure:** 

## NSN 5950-00-496-6835

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0