## NSN 5950-00-496-6898

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-496-6898

### **Reliability Indicator:**

Not established

### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.688 inches single mounting facility single center group

### Center To Center Distance Between Mounting Facilities Parallel To Width:

1.438 inches single mounting facility single center group

### Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

### Input-output Phase Relationship:

Three phase to three phase single component

### **Winding Shielding Method:**

Internal shield grounded to inclosure and core single component

#### **Body Length:**

2.312 inches

### **Body Width:**

2.062 inches

### **Body Height:**

3.125 inches

### **Maximum Operating Temp:**

105.0 degrees celsius

### Inclosure Type:

Hermetically sealed

### **Mounting Facility Quantity:**

4 single group

### **Mounting Method:**

Threaded stud single group

### **Winding Function And Quantity:**

1 primary single component and 4 secondary single component

#### Thready Qty Per Inch (tpi):

32 single group

### **Thread Size:**

0.138 inches single group

### **Winding Operating Current:**

2.0 amperes ac single component 4th secondary

### **Winding Operating Voltage:**

21.90 ac volts single component 4th secondary21.90 ac volts single component 3rd secondary

### **Thread Series Designator:**

Unc single group

### **Terminal Type And Quantity:**

15 solder stud

### Shelf Life:

N/a

# NSN 5950-00-496-6898

Power Transformer - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A058b0