

View Online at <https://aerobasegroup.com/nsn/5950-00-497-8603>

Reliability Indicator:

Not establishednot established

Overall Length:

4.315 inches 4.315 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group3.000 inches single mounting facility single center group

Overall Height:

2.100 inches 2.100 inches

Overall Width:

3.855 inches 3.855 inches

Mounting Hole Diameter:

0.187 inches single group0.187 inches single group

Frequency Rating:

400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single componentthree phase to three phase single component

Transformer Winding Connection Type:

Delta-deltadelta-delta

Winding Shielding Method:

Internal shield brought out to terminal single componentinternal shield brought out to terminal single component

Maximum Operating Temp:

170.0 degrees celsius170.0 degrees celsius

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Flange single group and flange single group and unthreaded hole single groupunthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

Winding Operating Current:

39.0 amperes ac single component single secondary

Winding Power Rating:

2.5 kilovolt-amperes single component single secondary

Winding Operating Voltage:

65.00 ac volts single component single secondary200.00 ac volts single component single primary

Terminal Type And Quantity:

7 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0