

View Online at <https://aerobasegroup.com/nsn/5950-00-497-9169>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.375 inches single mounting facility single center group

Overall Height:

3.875 inches

Overall Width:

2.380 inches

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to six phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

2.000 inches

Body Width:

1.880 inches

Body Height:

3.250 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

3.27 amperes ac single component single secondary

Winding Operating Voltage:

110.40 ac volts single component single primary and 5.45 ac volts single component single secondary 112.70 ac volts single component single primary and 115.00 ac volts single component single primary and 117.30 ac volts single component single primary and 119.60 ac volts single component single primary

Special Features:

Mtg on second end same as first end

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 turret and 18 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0