## NSN 5950-00-498-5442

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-498-5442

Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.250 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.375 inches single mounting facility single center group
Frequency Rating:
380.0 hertz single component and 420.0 hertz single component
Input-output Phase Relationship:
Three phase to three phase single component
Winding Shielding Method:
Internal shield grounded to inclosure and core single component
Body Length:
1.938 inches
Body Width:
1.812 inches
Body Height:
2.750 inches
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Winding Function And Quantity:
1 primary single component and 4 secondary single component
Thready Qty Per Inch (tpi):
32 single group
Thread Size:
0.138 inches single group
Winding Operating Current:
100.0 milliamperes ac single component 2nd secondary
Winding Operating Voltage:
115.00 ac volts single component single primary15.80 ac volts single component 4th secondary
Thread Series Designator:
Terminal Type And Quantity:
15 solder stud
Shelf Life:
N/a
Unit Of Measure:
-

## NSN 5950-00-498-5442

Power Transformer - Page 2 of 2

Demilitarization:

No

Fiig:

A058b0

