

View Online at <https://aerobasegroup.com/nsn/5950-00-500-7127>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.875 inches single mounting facility single center group0.875 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.813 inches single mounting facility single center group0.813 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal all componentsinternal shield brought out to terminal all components

Body Length:

1.219 inches 1.219 inches

Body Width:

1.219 inches 1.219 inches

Body Height:

1.781 inches 1.781 inches

Maximum Operating Temp:

110.0 degrees celsius110.0 degrees celsius

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded hole single groupthreaded hole single group

Winding Function And Quantity:

2 primary single component and 2 primary single component and 2 secondary single component2 secondary single component

Features Provided:

Color coded lead

Thread Size:

0.112 inches single group

Winding Operating Current:

0.2 milliamperes ac single component all secondary

Winding Operating Voltage:

2.64 ac volts single component all primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0