

View Online at <https://aerobasegroup.com/nsn/5950-00-500-7127>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.875 inches single mounting facility single center group0.875 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.813 inches single mounting facility single center group0.813 inches single mounting facility single center group

**Frequency Rating:**

400.0 hertz single component400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Winding Shielding Method:**

Internal shield brought out to terminal all componentsinternal shield brought out to terminal all components

**Body Length:**

1.219 inches 1.219 inches

**Body Width:**

1.219 inches 1.219 inches

**Body Height:**

1.781 inches 1.781 inches

**Maximum Operating Temp:**

110.0 degrees celsius110.0 degrees celsius

**Inclosure Type:**

Fully enclosedfully enclosed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded hole single groupthreaded hole single group

**Winding Function And Quantity:**

2 primary single component and 2 primary single component and 2 secondary single component2 secondary single component

**Features Provided:**

Color coded lead

**Thread Size:**

0.112 inches single group

**Winding Operating Current:**

0.2 milliamperes ac single component all secondary

**Winding Operating Voltage:**

2.64 ac volts single component all primary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

10 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0