

View Online at <https://aerobasegroup.com/nsn/5950-00-500-9024>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.380 inches single mounting facility single center group1.380 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.250 inches single mounting facility single center group1.250 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single componentinternal shield brought out to terminal single component

Body Length:

1.895 inches 1.895 inches

Body Width:

1.770 inches 1.770 inches

Body Height:

2.350 inches 2.350 inches

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 4 secondary single component4 secondary single component

Thread Size:

0.164 inches single group0.164 inches single group

Winding Operating Current:

99.0 milliamperes dc single component 2nd secondary

Winding Operating Voltage:

97.30 ac volts single component 1st secondary2.43 ac volts single component 3rd secondary31.80 ac volts single component 2nd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

11 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0