NSN 5950-00-501-0305

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-501-0305

Not established Overall Length: 6.750 inches Frequency Rating: 50.0 hertz single component and 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 6.750 inches Body Width: 5.094 inches Body Height: 5.594 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 3 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 28 single group Winding Operating Current: 7.5 amperes ac single component single secondary Winding Power Rating: 1.0 kilovolt-amperes single component single secondary Winding Operating Voltage: 115.00 ac volts single component single primary Special Features: Mtg holes spaced 120 degrees apart on 2.500 in radius Thread Series Designator: Unf single group Terminal Type And Quantity: 5 tab, solder lug	
Overall Length: 6.750 inches Frequency Rating: 50.0 hertz single component and 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 6.750 inches Body Width: 5.094 inches Body Height: 5.594 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 3 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 28 single group Winding Operating Current: 7.5 amperes ac single component single secondary Winding Power Rating: 1.0 kilovolt-amperes single component single secondary Winding Operating Voltage: 115.00 ac volts single component single primary Special Features: Mtg holes spaced 120 degrees apart on 2.500 in radius Thread Series Designator: Unf single group Terminal Type And Quantity: 5 tab, solder lug	Reliability Indicator:
6.750 inches Frequency Rating: 50.0 hertz single component and 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 6.750 inches Body Width: 5.094 inches Body Height: 5.594 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 3 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 28 single group Winding Operating Current: 7.5 amperes ac single component single secondary Winding Power Rating: 1.0 kilovolt-amperes single component single secondary Winding Operating Voltage: 115.00 ac volts single component single primary Special Features: Mtg holes spaced 120 degrees apart on 2.500 in radius Thread Series Designator: Unf single group Terminal Type And Quantity: 5 tab, solder lug	Not established
Frequency Rating: 50.0 hertz single component and 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 6.750 inches Body Width: 5.094 inches Body Height: 5.594 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 3 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 28 single group Winding Operating Current: 7.5 amperes ac single component single secondary Winding Power Rating: 1.0 kilovolt-amperes single component single secondary Winding Operating Voltage: 115.00 ac volts single component single primary Special Features: Mtg holes spaced 120 degrees apart on 2.500 in radius Thread Series Designator: Unf single group Terminal Type And Quantity: 5 tab, solder lug	
50.0 hertz single component and 60.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 6.750 inches Body Width: 5.094 inches Body Height: 5.594 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 3 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 28 single group Winding Operating Current: 7.5 amperes ac single component single secondary Winding Power Rating: 1.0 kilovolt-amperes single component single secondary Winding Operating Voltage: 115.00 ac volts single component single primary Special Features: Mtg holes spaced 120 degrees apart on 2.500 in radius Thread Series Designator: Unf single group Terminal Type And Quantity: 5 tab, solder lug	6.750 inches
Input-output Phase Relationship: Single phase to single phase single component Body Length: 6.750 inches Body Width: 5.094 inches Body Height: 5.594 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 3 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 28 single group Thread Size: 0.250 inches single group Winding Operating Current: 7.5 amperes ac single component single secondary Winding Operating Voltage: 115.00 ac volts single component single primary Special Features: Mtg holes spaced 120 degrees apart on 2.500 in radius Thread Series Designator: Unf single group Terminal Type And Quantity: 5 tab, solder lug	Frequency Rating:
Single phase to single phase single component Body Length: 6.750 inches Body Width: 5.094 inches Body Height: 5.594 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 3 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 28 single group Thread Size: 0.250 inches single group Winding Operating Current: 7.5 amperes ac single component single secondary Winding Power Rating: 1.0 kilovolt-amperes single component single secondary Winding Operating Voltage: 115.00 ac volts single component single primary Special Features: Mtg holes spaced 120 degrees apart on 2.500 in radius Thread Series Designator: Unf single group Terminal Type And Quantity: 5 tab, solder lug	50.0 hertz single component and 60.0 hertz single component
Body Length: 6.750 inches Body Width: 5.094 inches Body Height: 5.594 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 3 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 28 single group Thread Size: 0.250 inches single group Winding Operating Current: 7.5 amperes ac single component single secondary Winding Power Rating: 1.0 kilovolt-amperes single component single secondary Winding Operating Voltage: 115.00 ac volts single component single primary Special Features: Mtg holes spaced 120 degrees apart on 2.500 in radius Thread Series Designator: Unf single group Terminal Type And Quantity: 5 tab, solder lug	Input-output Phase Relationship:
6.750 inches Body Width: 5.094 inches Body Height: 5.594 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 3 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 28 single group Thread Size: 0.250 inches single group Winding Operating Current: 7.5 amperes ac single component single secondary Winding Power Rating: 1.0 kilovolt-amperes single component single secondary Winding Operating Voltage: 115.00 ac volts single component single primary Special Features: Mtg holes spaced 120 degrees apart on 2.500 in radius Thread Series Designator: Unf single group Terminal Type And Quantity: 5 tab, solder lug	Single phase to single phase single component
Body Width: 5.094 inches Body Height: 5.594 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 3 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 28 single group Thread Size: 0.250 inches single group Winding Operating Current: 7.5 amperes ac single component single secondary Winding Power Rating: 1.0 kilovolt-amperes single component single secondary Winding Operating Voltage: 115.00 ac volts single component single primary Special Features: Mtg holes spaced 120 degrees apart on 2.500 in radius Thread Series Designator: Unf single group Terminal Type And Quantity: 5 tab, solder lug	Body Length:
Body Height: 5.594 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 3 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 28 single group Thread Size: 0.250 inches single group Winding Operating Current: 7.5 amperes ac single component single secondary Winding Power Rating: 1.0 kilovolt-amperes single component single secondary Winding Operating Voltage: 115.00 ac volts single component single primary Special Features: Mtg holes spaced 120 degrees apart on 2.500 in radius Thread Series Designator: Unf single group Terminal Type And Quantity: 5 tab, solder lug	6.750 inches
Body Height: 5.594 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 3 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 28 single group Thread Size: 0.250 inches single group Winding Operating Current: 7.5 amperes ac single component single secondary Winding Power Rating: 1.0 kilovolt-amperes single component single secondary Winding Operating Voltage: 115.00 ac volts single component single primary Special Features: Mtg holes spaced 120 degrees apart on 2.500 in radius Thread Series Designator: Unf single group Terminal Type And Quantity: 5 tab, solder lug	Body Width:
Inclosure Type: Fully enclosed Mounting Facility Quantity: 3 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 28 single group Thread Size: 0.250 inches single group Winding Operating Current: 7.5 amperes ac single component single secondary Winding Power Rating: 1.0 kilovolt-amperes single component single secondary Winding Operating Voltage: 115.00 ac volts single component single primary Special Features: Mtg holes spaced 120 degrees apart on 2.500 in radius Thread Series Designator: Unf single group Terminal Type And Quantity: 5 tab, solder lug	5.094 inches
Inclosure Type: Fully enclosed Mounting Facility Quantity: 3 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 28 single group Thread Size: 0.250 inches single group Winding Operating Current: 7.5 amperes ac single component single secondary Winding Power Rating: 1.0 kilovolt-amperes single component single secondary Winding Operating Voltage: 115.00 ac volts single component single primary Special Features: Mtg holes spaced 120 degrees apart on 2.500 in radius Thread Series Designator: Unf single group Terminal Type And Quantity: 5 tab, solder lug	Body Height:
Fully enclosed Mounting Facility Quantity: 3 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 28 single group Thread Size: 0.250 inches single group Winding Operating Current: 7.5 amperes ac single component single secondary Winding Power Rating: 1.0 kilovolt-amperes single component single secondary Winding Operating Voltage: 115.00 ac volts single component single primary Special Features: Mtg holes spaced 120 degrees apart on 2.500 in radius Thread Series Designator: Unf single group Terminal Type And Quantity: 5 tab, solder lug	5.594 inches
Mounting Facility Quantity: 3 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 28 single group Thread Size: 0.250 inches single group Winding Operating Current: 7.5 amperes ac single component single secondary Winding Power Rating: 1.0 kilovolt-amperes single component single secondary Winding Operating Voltage: 115.00 ac volts single component single primary Special Features: Mtg holes spaced 120 degrees apart on 2.500 in radius Thread Series Designator: Unf single group Terminal Type And Quantity: 5 tab, solder lug	Inclosure Type:
Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 28 single group Thread Size: 0.250 inches single group Winding Operating Current: 7.5 amperes ac single component single secondary Winding Power Rating: 1.0 kilovolt-amperes single component single secondary Winding Operating Voltage: 115.00 ac volts single component single primary Special Features: Mtg holes spaced 120 degrees apart on 2.500 in radius Thread Series Designator: Unf single group Terminal Type And Quantity: 5 tab, solder lug	Fully enclosed
Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 28 single group Thread Size: 0.250 inches single group Winding Operating Current: 7.5 amperes ac single component single secondary Winding Power Rating: 1.0 kilovolt-amperes single component single secondary Winding Operating Voltage: 115.00 ac volts single component single primary Special Features: Mtg holes spaced 120 degrees apart on 2.500 in radius Thread Series Designator: Unf single group Terminal Type And Quantity: 5 tab, solder lug	Mounting Facility Quantity:
Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 28 single group Thread Size: 0.250 inches single group Winding Operating Current: 7.5 amperes ac single component single secondary Winding Power Rating: 1.0 kilovolt-amperes single component single secondary Winding Operating Voltage: 115.00 ac volts single component single primary Special Features: Mtg holes spaced 120 degrees apart on 2.500 in radius Thread Series Designator: Unf single group Terminal Type And Quantity: 5 tab, solder lug	3 single group
Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 28 single group Thread Size: 0.250 inches single group Winding Operating Current: 7.5 amperes ac single component single secondary Winding Power Rating: 1.0 kilovolt-amperes single component single secondary Winding Operating Voltage: 115.00 ac volts single component single primary Special Features: Mtg holes spaced 120 degrees apart on 2.500 in radius Thread Series Designator: Unf single group Terminal Type And Quantity: 5 tab, solder lug	Mounting Method:
1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 28 single group Thread Size: 0.250 inches single group Winding Operating Current: 7.5 amperes ac single component single secondary Winding Power Rating: 1.0 kilovolt-amperes single component single secondary Winding Operating Voltage: 115.00 ac volts single component single primary Special Features: Mtg holes spaced 120 degrees apart on 2.500 in radius Thread Series Designator: Unf single group Terminal Type And Quantity: 5 tab, solder lug	Threaded hole single group
Thready Qty Per Inch (tpi): 28 single group Thread Size: 0.250 inches single group Winding Operating Current: 7.5 amperes ac single component single secondary Winding Power Rating: 1.0 kilovolt-amperes single component single secondary Winding Operating Voltage: 115.00 ac volts single component single primary Special Features: Mtg holes spaced 120 degrees apart on 2.500 in radius Thread Series Designator: Unf single group Terminal Type And Quantity: 5 tab, solder lug	Winding Function And Quantity:
Thread Size: 0.250 inches single group Winding Operating Current: 7.5 amperes ac single component single secondary Winding Power Rating: 1.0 kilovolt-amperes single component single secondary Winding Operating Voltage: 115.00 ac volts single component single primary Special Features: Mtg holes spaced 120 degrees apart on 2.500 in radius Thread Series Designator: Unf single group Terminal Type And Quantity: 5 tab, solder lug	1 primary, variable autotransformer type single component
Thread Size: 0.250 inches single group Winding Operating Current: 7.5 amperes ac single component single secondary Winding Power Rating: 1.0 kilovolt-amperes single component single secondary Winding Operating Voltage: 115.00 ac volts single component single primary Special Features: Mtg holes spaced 120 degrees apart on 2.500 in radius Thread Series Designator: Unf single group Terminal Type And Quantity: 5 tab, solder lug	Thready Qty Per Inch (tpi):
0.250 inches single group Winding Operating Current: 7.5 amperes ac single component single secondary Winding Power Rating: 1.0 kilovolt-amperes single component single secondary Winding Operating Voltage: 115.00 ac volts single component single primary Special Features: Mtg holes spaced 120 degrees apart on 2.500 in radius Thread Series Designator: Unf single group Terminal Type And Quantity: 5 tab, solder lug	28 single group
Winding Operating Current: 7.5 amperes ac single component single secondary Winding Power Rating: 1.0 kilovolt-amperes single component single secondary Winding Operating Voltage: 115.00 ac volts single component single primary Special Features: Mtg holes spaced 120 degrees apart on 2.500 in radius Thread Series Designator: Unf single group Terminal Type And Quantity: 5 tab, solder lug	Thread Size:
7.5 amperes ac single component single secondary Winding Power Rating: 1.0 kilovolt-amperes single component single secondary Winding Operating Voltage: 115.00 ac volts single component single primary Special Features: Mtg holes spaced 120 degrees apart on 2.500 in radius Thread Series Designator: Unf single group Terminal Type And Quantity: 5 tab, solder lug	0.250 inches single group
Winding Power Rating: 1.0 kilovolt-amperes single component single secondary Winding Operating Voltage: 115.00 ac volts single component single primary Special Features: Mtg holes spaced 120 degrees apart on 2.500 in radius Thread Series Designator: Unf single group Terminal Type And Quantity: 5 tab, solder lug	Winding Operating Current:
1.0 kilovolt-amperes single component single secondary Winding Operating Voltage: 115.00 ac volts single component single primary Special Features: Mtg holes spaced 120 degrees apart on 2.500 in radius Thread Series Designator: Unf single group Terminal Type And Quantity: 5 tab, solder lug	7.5 amperes ac single component single secondary
Winding Operating Voltage: 115.00 ac volts single component single primary Special Features: Mtg holes spaced 120 degrees apart on 2.500 in radius Thread Series Designator: Unf single group Terminal Type And Quantity: 5 tab, solder lug	Winding Power Rating:
115.00 ac volts single component single primary Special Features: Mtg holes spaced 120 degrees apart on 2.500 in radius Thread Series Designator: Unf single group Terminal Type And Quantity: 5 tab, solder lug	1.0 kilovolt-amperes single component single secondary
Special Features: Mtg holes spaced 120 degrees apart on 2.500 in radius Thread Series Designator: Unf single group Terminal Type And Quantity: 5 tab, solder lug	Winding Operating Voltage:
Mtg holes spaced 120 degrees apart on 2.500 in radius Thread Series Designator: Unf single group Terminal Type And Quantity: 5 tab, solder lug	115.00 ac volts single component single primary
Thread Series Designator: Unf single group Terminal Type And Quantity: 5 tab, solder lug	Special Features:
Unf single group Terminal Type And Quantity: 5 tab, solder lug	Mtg holes spaced 120 degrees apart on 2.500 in radius
Terminal Type And Quantity: 5 tab, solder lug	Thread Series Designator:
5 tab, solder lug	Unf single group
-	Terminal Type And Quantity:
-	5 tab, solder lug
Shell Life.	Shelf Life:
N/a	N/a

--

Unit Of Measure:

NSN 5950-00-501-0305

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0