

View Online at <https://aerobasegroup.com/nsn/5950-00-504-0452>

Reliability Indicator:

Not establishednot established

Frequency Rating:

380.0 hertz single component and 380.0 hertz single component and 420.0 hertz single component420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Body Length:

Between 0.780 inches and 0.780 inches and 0.790 inches 0.790 inches

Body Width:

Between 0.620 inches and 0.620 inches and 0.630 inches 0.630 inches

Body Height:

Between 0.660 inches and 0.660 inches and 0.670 inches 0.670 inches

Maximum Operating Temp:

130.0 degrees celsius130.0 degrees celsius

Inclosure Type:

Fully enclosedfully enclosed

Mounting Method:

Terminal single groupterminal single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

Winding Operating Current:

125.0 milliamperes ac single component single secondary

Winding Operating Voltage:

0.39 ac volts single component single primary and 7.00 ac volts single component single primary

Test Data Document:

35351-151690 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0