

View Online at <https://aerobasegroup.com/nsn/5950-00-504-0452>

**Reliability Indicator:**

Not establishednot established

**Frequency Rating:**

380.0 hertz single component and 380.0 hertz single component and 420.0 hertz single component420.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Body Length:**

Between 0.780 inches and 0.780 inches and 0.790 inches 0.790 inches

**Body Width:**

Between 0.620 inches and 0.620 inches and 0.630 inches 0.630 inches

**Body Height:**

Between 0.660 inches and 0.660 inches and 0.670 inches 0.670 inches

**Maximum Operating Temp:**

130.0 degrees celsius130.0 degrees celsius

**Inclosure Type:**

Fully enclosedfully enclosed

**Mounting Method:**

Terminal single groupterminal single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

**Winding Operating Current:**

125.0 milliamperes ac single component single secondary

**Winding Operating Voltage:**

0.39 ac volts single component single primary and 7.00 ac volts single component single primary

**Test Data Document:**

35351-151690 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

5 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0