

View Online at <https://aerobasegroup.com/nsn/5950-00-504-0475>

Reliability Indicator:

Not establishednot established

Overall Length:

1.830 inches 1.830 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.250 inches single mounting facility single center group1.250 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.469 inches single mounting facility single center group1.469 inches single mounting facility single center group

Overall Height:

1.150 inches 1.150 inches

Overall Width:

1.469 inches 1.469 inches

Mounting Hole Diameter:

0.094 inches single group0.094 inches single group

Frequency Rating:

380.0 hertz single component and 380.0 hertz single component and 420.0 hertz single component420.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single componentthree phase to three phase single component

Transformer Winding Connection Type:

Wye-wyewye-wye

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single componentinternal shield grounded to core and brought out to terminal single component

Maximum Operating Temp:

105.0 degrees celsius105.0 degrees celsius

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Flange single group and flange single group and unthreaded hole single groupunthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

Features Provided:

Tinned wire leads

Winding Operating Current:

73.0 milliamperes ac single component single secondary

Winding Operating Voltage:

27.00 ac volts single component single secondary

Terminal Type And Quantity:

9 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0