

View Online at <https://aerobasegroup.com/nsn/5950-00-504-6505>

Reliability Indicator:

Not establishednot established

Overall Length:

6.000 inches 6.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.828 inches single mounting facility single center group and 4.828 inches single mounting facility single center group and 4.928 inches single mounting facility single center group4.928 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.703 inches single mounting facility single center group and 3.703 inches single mounting facility single center group and 3.944 inches single mounting facility single center group3.944 inches single mounting facility single center group

Overall Height:

5.250 inches 5.250 inches

Overall Width:

4.875 inches 4.875 inches

Frequency Rating:

50.0 hertz single component and 50.0 hertz single component and 1.0 kilohertz single component1.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

2 primary single component and 2 primary single component and 6 secondary single component6 secondary single component

Thread Size:

0.250 inches single group0.250 inches single group

Winding Operating Current:

750.0 milliamperes dc single component 3rd secondary

Winding Operating Voltage:

246.00 ac volts single component 1st secondary156.00 ac volts single component 3rd secondary176.00 ac volts single component 2nd secondary

Special Features:

2 primary windings; 6 secondary windings

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

17 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0