

View Online at <https://aerobasegroup.com/nsn/5950-00-504-7381>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.875 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

7.000 inches

Body Width:

4.750 inches

Body Height:

5.875 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.190 inches single group

Winding Operating Current:

550.0 milliamperes ac single component single secondary

Winding Operating Voltage:

95.00 ac volts single component single primary and 5.00 ac volts single component single secondary and 105.00 ac volts single component single primary and 10.00 ac volts single component single secondary and 115.00 ac volts single component single primary and 15.00 ac volts single component single secondary and 125.00 ac volts single component single primary and 162.00 ac volts single component single secondary and 190.00 ac volts single component single primary and 210.00 ac volts single component single primary and 230.00 ac volts single component single primary and 250.00 ac volts single component single primary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

15 standoff insulator

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fig:

A058b0