NSN 5950-00-504-8960

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-504-8960

Reliability Indicator: Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 1.750 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.470 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Length: 1.750 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width:
1.750 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width:
Center To Center Distance Between Mounting Facilities Parallel To Width:
-
1 470 inches single mounting facility single center group
Frequency Rating:
50.0 hertz single component or 60.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield grounded to inclosure single component
Body Length:
2.810 inches
Body Width:
2.440 inches
Body Height:
3.820 inches
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Thready Qty Per Inch (tpi):
32 single group
Thread Size:
0.138 inches single group
Winding Operating Current:
30.0 milliamperes ac single component single secondary
Winding Operating Voltage:
235.00 ac volts single component single secondary120.00 ac volts single component single primary
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
4 standoff, solder lug
Shelf Life:
N/a
Unit Of Measure:

NSN 5950-00-504-8960

Power Transformer - Page 2 of 2

Demilitarization:

No

Fiig:

A058b0

