Audio Frequency Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-504-9155

Reliabili	ity Indicator:
Not esta	blished
Center 1	Го Center Distance Between Mounting Facilities Parallel To Length
0.875 ind	ches single mounting facility single center group
Center 1	Fo Center Distance Between Mounting Facilities Parallel To Width:
0.875 ind	ches single mounting facility single center group
Impedar	nce Rating In Ohms:
10000.0	single component single secondary
Frequen	ncy Rating:
400.0 he	ertz single component and 3.0 kilohertz single component
Maximu	m Transformer Power Rating:
100.0 mi	illiwatts single component
Body Le	ength:
1.781 ind	ches
Body W	idth:
1.281 ind	ches
Body He	eight:
2.312 inc	ches
Inclosur	е Туре:
Hermetic	cally sealed
Mountin	ng Facility Quantity:
4 single	group
Mountin	ng Method:
Threade	d stud single group
Winding	Function And Quantity:
2 primar	y single component and 1 secondary single component
Thready	v Qty Per Inch (tpi):
32 single	s group
Thread \$	Size:
0.164 ind	ches single group
Winding	g Operating Current:
5.0 millia	amperes dc single component all primary
Thread \$	Series Designator:
Unc sing	le group
Termina	Il Type And Quantity:
7 solder	stud
Shelf Lif	fe:
N/a	
Unit Of I	Measure:
Demilita	rization:
No	

NSN 5950-00-504-9155 Audio Frequency Transformer - Page 2 of 2

Fiig: A058b0

