

View Online at <https://aerobasegroup.com/nsn/5950-00-506-6742>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

4.500 inches single mounting facility single center group4.500 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.750 inches single mounting facility single center group2.750 inches single mounting facility single center group

**Frequency Rating:**

400.0 hertz single component400.0 hertz single component

**Input-output Phase Relationship:**

Three phase to three phase single componentthree phase to three phase single component

**Transformer Winding Connection Type:**

Wye-wyewye-wye

**Body Length:**

6.000 inches 6.000 inches

**Body Width:**

4.000 inches 4.000 inches

**Body Height:**

3.500 inches 3.500 inches

**Inclosure Type:**

Hermetically sealedhermetically sealed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded hole single groupthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component

**Thread Size:**

0.250 inches single group

**Winding Operating Current:**

32.0 amperes ac single component 1st secondary

**Winding Operating Voltage:**

30.00 ac volts single component 1st secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

9 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0