# NSN 5950-00-506-6742

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-506-6742

## **Reliability Indicator:**

Not establishednot established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

4.500 inches single mounting facility single center group4.500 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.750 inches single mounting facility single center group2.750 inches single mounting facility single center group

#### Frequency Rating:

400.0 hertz single component400.0 hertz single component

#### Input-output Phase Relationship:

Three phase to three phase single componentthree phase to three phase single component

#### **Transformer Winding Connection Type:**

Wye-wyewye-wye

**Body Length:** 

6.000 inches 6.000 inches

**Body Width:** 

4.000 inches 4.000 inches

**Body Height:** 

3.500 inches 3.500 inches

**Inclosure Type:** 

Hermetically sealedhermetically sealed

# **Mounting Facility Quantity:**

4 single group4 single group

#### **Mounting Method:**

Threaded hole single groupthreaded hole single group

# **Winding Function And Quantity:**

1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component

# Thread Size:

0.250 inches single group

#### **Winding Operating Current:**

32.0 amperes ac single component 1st secondary

# Winding Operating Voltage:

30.00 ac volts single component 1st secondary

# **Thread Series Designator:**

Unc single group

## **Terminal Type And Quantity:**

9 tab, solder lug

Shelf Life:

N/a

# **Unit Of Measure:**

--

#### **Demilitarization:**

No

# NSN 5950-00-506-6742

Power Transformer - Page 2 of 2



Fiig:

A058b0