

View Online at <https://aerobasegroup.com/nsn/5950-00-506-7077>

Reliability Indicator:

Not establishednot established

Hazardous Locations/environmental Protection:

Vibration resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.438 inches single mounting facility single center group2.438 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group2.000 inches single mounting facility single center group

Mounting Hole Diameter:

0.148 inches single group and 0.148 inches single group and 0.165 inches single group0.165 inches single group

Frequency Rating:

400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Three phase to single phase single component and three phase to single phase single component and three phase to three phase single componentthree phase to three phase single component

Winding Shielding Method:

Core grounded single componentcore grounded single component

Body Length:

3.630 inches 3.630 inches

Body Width:

2.750 inches 2.750 inches

Body Height:

1.500 inches 1.500 inches

Maximum Operating Temp:

130.0 degrees celsius130.0 degrees celsius

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Flange single group and flange single group and unthreaded hole single groupunthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 4 secondary single component4 secondary single component

Winding Operating Current:

4.5 amperes dc single component 1st secondary

Winding Operating Voltage:

36.00 ac volts single component 4th secondary23.00 ac volts single component 2nd secondary

Special Features:

Rectified current; tab solder lug terminals are tin plated

Terminal Type And Quantity:

15 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0