

View Online at <https://aerobasegroup.com/nsn/5950-00-508-8018>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.188 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

2.938 inches

Body Width:

2.656 inches

Body Height:

2.875 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

70.0 milliamperes ac single component 4th secondary

Winding Operating Voltage:

6.40 ac volts single component 2nd secondary 80.00 ac volts single component 4th secondary 6.40 ac volts single component 3rd secondary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

12 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0