

View Online at <https://aerobasegroup.com/nsn/5950-00-513-3844>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.000 inches single mounting facility single center group2.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group2.000 inches single mounting facility single center group

Mounting Slot Width:

0.138 inches single group0.138 inches single group

Frequency Rating:

47.0 hertz single component and 47.0 hertz single component and 63.0 hertz single component63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

Body Length:

2.530 inches 2.530 inches

Body Width:

2.310 inches 2.310 inches

Body Height:

3.060 inches 3.060 inches

Maximum Operating Temp:

50.0 degrees celsius50.0 degrees celsius

Inclosure Type:

Openopen

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Flange single group and flange single group and slot single groupslot single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 3 secondary single component3 secondary single component

Winding Operating Current:

250.0 milliamperes ac single component 1st secondary

Winding Operating Voltage:

54.00 ac volts single component 2nd secondary

Terminal Type And Quantity:

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0