

View Online at <https://aerobasegroup.com/nsn/5950-00-513-3844>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.000 inches single mounting facility single center group2.000 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.000 inches single mounting facility single center group2.000 inches single mounting facility single center group

**Mounting Slot Width:**

0.138 inches single group0.138 inches single group

**Frequency Rating:**

47.0 hertz single component and 47.0 hertz single component and 63.0 hertz single component63.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

**Body Length:**

2.530 inches 2.530 inches

**Body Width:**

2.310 inches 2.310 inches

**Body Height:**

3.060 inches 3.060 inches

**Maximum Operating Temp:**

50.0 degrees celsius50.0 degrees celsius

**Inclosure Type:**

Openopen

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Flange single group and flange single group and slot single groupslot single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 3 secondary single component3 secondary single component

**Winding Operating Current:**

250.0 milliamperes ac single component 1st secondary

**Winding Operating Voltage:**

54.00 ac volts single component 2nd secondary

**Terminal Type And Quantity:**

11 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0