

View Online at <https://aerobasegroup.com/nsn/5950-00-513-4301>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.300 inches single mounting facility single center group1.300 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.900 inches single mounting facility single center group0.900 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single componentinternal shield grounded to core and brought out to terminal single component

Body Length:

1.550 inches 1.550 inches

Body Width:

0.870 inches 0.870 inches

Body Height:

1.150 inches 1.150 inches

End Application:

Aircraft: f-111; galaxy c-5; eagle, f-15; missile, mx peacekeeperaircraft: f-111; galaxy c-5; eagle, f-15; missile, mx peacekeeper

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded hole single groupthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

Features Provided:

Color coded lead

Thread Size:

0.112 inches single group0.112 inches single group

Winding Operating Current:

3.0 amperes ac single component single secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

60.00 ac volts single component single primary

Special Features:

Weapon system essential

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0