

View Online at <https://aerobasegroup.com/nsn/5950-00-515-2973>

Reliability Indicator:

Not establishednot established

Mounting Hole Diameter:

0.170 inches single group and 0.170 inches single group and 0.200 inches single group0.200 inches single group

Frequency Rating:

47.0 hertz single component and 47.0 hertz single component and 63.0 hertz single component63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

Body Length:

2.280 inches 2.280 inches

Body Width:

1.890 inches 1.890 inches

Body Height:

2.750 inches 2.750 inches

Distance Between Mounting Facility Centers:

2.820 inches single mounting facility single center group and 2.820 inches single mounting facility single center group and 2.860 inches single mounting facility single center group2.860 inches single mounting facility single center group

Inclosure Type:

Openopen

Mounting Facility Quantity:

2 single group2 single group

Mounting Method:

Flange single group and flange single group and unthreaded hole single groupunthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component

Winding Operating Current:

100.0 milliamperes dc single component 2nd secondary

Winding Operating Voltage:

36.00 ac volts single component 2nd secondary22.00 ac volts single component 1st secondary

Special Features:

Output currents are stated as rectified

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0