

View Online at <https://aerobasegroup.com/nsn/5950-00-517-8808>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.875 inches single mounting facility single center group2.875 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.718 inches single mounting facility single center group2.718 inches single mounting facility single center group

**Frequency Rating:**

400.0 hertz single component400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure and core single componentinternal shield grounded to inclosure and core single component

**Body Length:**

3.375 inches 3.375 inches

**Body Width:**

3.100 inches 3.100 inches

**Body Height:**

0.950 inches 0.950 inches

**Inclosure Type:**

Hermetically sealedhermetically sealed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded hole single groupthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component

**Thready Qty Per Inch (tpi):**

32 single group32 single group

**Thread Size:**

0.138 inches single group0.138 inches single group

**Winding Operating Current:**

1.125 amperes dc single component 1st primary

**Winding Operating Voltage:**

13.95 ac volts single component 1st secondary and 115.00 ac volts single component single primary110.00 ac volts single component 2nd secondary32.05 ac volts single component 1st secondary and 46.00 ac volts single component 1st secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

9 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0