

View Online at <https://aerobasegroup.com/nsn/5950-00-518-0027>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.000 inches

Body Width:

2.500 inches

Body Height:

2.875 inches

Inclosure Type:

Partially enclosed, double shell

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

40.0 milliamperes ac single component 2nd secondary

Winding Operating Voltage:

6.30 ac volts single component 1st secondary 5.00 ac volts single component 3rd secondary 650.00 ac volts single component 2nd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0