

View Online at <https://aerobasegroup.com/nsn/5950-00-518-0196>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.760 inches single mounting facility single center group3.760 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group3.000 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component or 50.0 hertz single component or 60.0 hertz single component60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

Body Length:

5.000 inches 5.000 inches

Body Width:

4.260 inches 4.260 inches

Body Height:

5.400 inches 5.400 inches

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

Thready Qty Per Inch (tpi):

32 single group32 single group

Thread Size:

0.138 inches single group0.138 inches single group

Winding Operating Current:

240.0 milliamperes ac single component single secondary

Winding Operating Voltage:

750.00 ac volts single component single secondary120.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0