NSN 5950-00-518-0392

Reactor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-518-0392

Note established Center To Center Distance Between Mounting Facilities Parallel To Length: 1.060 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 2.937 inches single mounting facility single center group Mounting Hole Diameter: 0.188 inches single group Inductance Type: Fixed Inductance Rating: 6.80 henry single component single winding Body Length: 2.438 inches Body Width: 1.938 inches Body Height: 1.812 inches Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Dc Resistance Rating In Ohms: 90.000 single component single winding Terminal Type And Quantity: 2 solder stud Shelf Life: N/a Unit Of Measure:	Reliability Indicator:
Center To Center Distance Between Mounting Facilities Parallel To Length: 1.060 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 2.937 inches single mounting facility single center group Mounting Hole Diameter: 0.188 inches single group Inductance Type: Fixed Inductance Rating: 6.80 henry single component single winding Body Length: 2.438 inches Body Width: 1.938 inches Body Height: 1.812 inches Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Dc Resistance Rating In Ohms: 90.000 single component single winding Terminal Type And Quantity: 2 solder stud Shelf Life: N/a	•
1.060 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 2.937 inches single mounting facility single center group Mounting Hole Diameter: 0.188 inches single group Inductance Type: Fixed Inductance Rating: 6.80 henry single component single winding Body Length: 2.438 inches Body Width: 1.938 inches Body Height: 1.812 inches Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Dc Resistance Rating In Ohms: 90.000 single component single winding Terminal Type And Quantity: 2 solder stud Shelf Life: N/a	
Center To Center Distance Between Mounting Facilities Parallel To Width: 2.937 inches single mounting facility single center group Mounting Hole Diameter: 0.188 inches single group Inductance Type: Fixed Inductance Rating: 6.80 henry single component single winding Body Length: 2.438 inches Body Width: 1.938 inches Body Height: 1.812 inches Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Dc Resistance Rating In Ohms: 90.000 single component single winding Terminal Type And Quantity: 2 solder stud Shelf Life: N/a	-
2.937 inches single mounting facility single center group Mounting Hole Diameter: 0.188 inches single group Inductance Type: Fixed Inductance Rating: 6.80 henry single component single winding Body Length: 2.438 inches Body Width: 1.938 inches Body Height: 1.812 inches Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Dc Resistance Rating In Ohms: 90.000 single component single winding Terminal Type And Quantity: 2 solder stud Shelf Life: N/a	
Mounting Hole Diameter: 0.188 inches single group Inductance Type: Fixed Inductance Rating: 6.80 henry single component single winding Body Length: 2.438 inches Body Width: 1.938 inches Body Height: 1.812 inches Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Dc Resistance Rating In Ohms: 90.000 single component single winding Terminal Type And Quantity: 2 solder stud Shelf Life: N/a	
Inductance Type: Fixed Inductance Rating: 6.80 henry single component single winding Body Length: 2.438 inches Body Width: 1.938 inches Body Height: 1.812 inches Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Dc Resistance Rating In Ohms: 90.000 single component single winding Terminal Type And Quantity: 2 solder stud Shelf Life: N/a	
Inductance Type: Fixed Inductance Rating: 6.80 henry single component single winding Body Length: 2.438 inches Body Width: 1.938 inches Body Height: 1.812 inches Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Dc Resistance Rating In Ohms: 90.000 single component single winding Terminal Type And Quantity: 2 solder stud Shelf Life: N/a	-
Fixed Inductance Rating: 6.80 henry single component single winding Body Length: 2.438 inches Body Width: 1.938 inches Body Height: 1.812 inches Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Dc Resistance Rating In Ohms: 90.000 single component single winding Terminal Type And Quantity: 2 solder stud Shelf Life: N/a	
Inductance Rating: 6.80 henry single component single winding Body Length: 2.438 inches Body Width: 1.938 inches Body Height: 1.812 inches Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Dc Resistance Rating In Ohms: 90.000 single component single winding Terminal Type And Quantity: 2 solder stud Shelf Life: N/a	
6.80 henry single component single winding Body Length: 2.438 inches Body Width: 1.938 inches Body Height: 1.812 inches Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Dc Resistance Rating In Ohms: 90.000 single component single winding Terminal Type And Quantity: 2 solder stud Shelf Life: N/a	
Body Length: 2.438 inches Body Width: 1.938 inches Body Height: 1.812 inches Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Dc Resistance Rating In Ohms: 90.000 single component single winding Terminal Type And Quantity: 2 solder stud Shelf Life: N/a	
2.438 inches Body Width: 1.938 inches Body Height: 1.812 inches Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Dc Resistance Rating In Ohms: 90.000 single component single winding Terminal Type And Quantity: 2 solder stud Shelf Life: N/a	
Body Width: 1.938 inches Body Height: 1.812 inches Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Dc Resistance Rating In Ohms: 90.000 single component single winding Terminal Type And Quantity: 2 solder stud Shelf Life: N/a	
1.938 inches Body Height: 1.812 inches Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Dc Resistance Rating In Ohms: 90.000 single component single winding Terminal Type And Quantity: 2 solder stud Shelf Life: N/a	
Body Height: 1.812 inches Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Dc Resistance Rating In Ohms: 90.000 single component single winding Terminal Type And Quantity: 2 solder stud Shelf Life: N/a	
Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Dc Resistance Rating In Ohms: 90.000 single component single winding Terminal Type And Quantity: 2 solder stud Shelf Life: N/a	
Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Dc Resistance Rating In Ohms: 90.000 single component single winding Terminal Type And Quantity: 2 solder stud Shelf Life: N/a	
1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Dc Resistance Rating In Ohms: 90.000 single component single winding Terminal Type And Quantity: 2 solder stud Shelf Life: N/a	
Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Dc Resistance Rating In Ohms: 90.000 single component single winding Terminal Type And Quantity: 2 solder stud Shelf Life: N/a	
Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Dc Resistance Rating In Ohms: 90.000 single component single winding Terminal Type And Quantity: 2 solder stud Shelf Life: N/a	
Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Dc Resistance Rating In Ohms: 90.000 single component single winding Terminal Type And Quantity: 2 solder stud Shelf Life: N/a	**
4 single group Mounting Method: Flange single group and unthreaded hole single group Dc Resistance Rating In Ohms: 90.000 single component single winding Terminal Type And Quantity: 2 solder stud Shelf Life: N/a	
Mounting Method: Flange single group and unthreaded hole single group Dc Resistance Rating In Ohms: 90.000 single component single winding Terminal Type And Quantity: 2 solder stud Shelf Life: N/a	
Flange single group and unthreaded hole single group Dc Resistance Rating In Ohms: 90.000 single component single winding Terminal Type And Quantity: 2 solder stud Shelf Life: N/a	
Dc Resistance Rating In Ohms: 90.000 single component single winding Terminal Type And Quantity: 2 solder stud Shelf Life: N/a	-
90.000 single component single winding Terminal Type And Quantity: 2 solder stud Shelf Life: N/a	
Terminal Type And Quantity: 2 solder stud Shelf Life: N/a	-
2 solder stud Shelf Life: N/a	90.000 single component single winding
Shelf Life: N/a	Terminal Type And Quantity:
N/a	2 solder stud
	Shelf Life:
Unit Of Measure:	N/a
	Unit Of Measure:
	
Demilitarization:	Demilitarization:
No	No
	Fiig:
	A058b0
-	Fiig:
Fiig:	A058b0