NSN 5950-00-518-0706

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-518-0706

Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.297 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.859 inches single mounting facility single center group
Frequency Rating:
57.0 hertz single component and 63.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Body Length:
3.062 inches
Body Width:
2.625 inches
Body Height:
4.250 inches
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Winding Function And Quantity:
2 primary single component and 1 secondary single component
Thready Qty Per Inch (tpi):
32 single group
Thread Size:

0.164 inches single group

Winding Operating Current:

2.0 amperes ac single component single secondary

Winding Power Rating:

60.0 volts-amperes single component single secondary

Winding Operating Voltage:

30.00 ac volts single component single secondary

Test Data Document:

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 solder stud

Shelf Life:

N/a

NSN 5950-00-518-0706

Power Transformer - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A058b0