

View Online at <https://aerobasegroup.com/nsn/5950-00-518-1053>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.750 inches single mounting facility single center group2.750 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.438 inches single mounting facility single center group2.438 inches single mounting facility single center group

**Mounting Hole Diameter:**

0.250 inches single group0.250 inches single group

**Frequency Rating:**

400.0 hertz single component400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

**Body Length:**

3.375 inches 3.375 inches

**Body Width:**

3.062 inches 3.062 inches

**Body Height:**

3.938 inches 3.938 inches

**Inclosure Type:**

Fully enclosedfully enclosed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Unthreaded hole single groupunthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 5 secondary single component5 secondary single component

**Winding Operating Current:**

6.2 amperes dc single component 4th secondary

**Winding Operating Voltage:**

6.30 ac volts single component 4th secondary45.00 ac volts single component 3rd secondary

**Special Features:**

1primary winding, five secondary windings; secondary current has been rectified

**Terminal Type And Quantity:**

16 standoff insulator

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0