

View Online at <https://aerobasegroup.com/nsn/5950-00-518-1053>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.750 inches single mounting facility single center group2.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.438 inches single mounting facility single center group2.438 inches single mounting facility single center group

Mounting Hole Diameter:

0.250 inches single group0.250 inches single group

Frequency Rating:

400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

Body Length:

3.375 inches 3.375 inches

Body Width:

3.062 inches 3.062 inches

Body Height:

3.938 inches 3.938 inches

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Unthreaded hole single groupunthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 5 secondary single component5 secondary single component

Winding Operating Current:

6.2 amperes dc single component 4th secondary

Winding Operating Voltage:

6.30 ac volts single component 4th secondary45.00 ac volts single component 3rd secondary

Special Features:

1primary winding, five secondary windings; secondary current has been rectified

Terminal Type And Quantity:

16 standoff insulator

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0