

View Online at <https://aerobasegroup.com/nsn/5950-00-518-1922>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.750 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

6.125 inches

Body Width:

4.375 inches

Body Height:

5.250 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 3 secondary single component

Thread Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

6.7 amperes ac single component 3rd secondary

Winding Operating Voltage:

5.00 ac volts single component 2nd secondary 470.00 ac volts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

11 standoff insulator

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0