## NSN 5950-00-518-3347

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-518-3347

| Reliability Indicator:  |
|---|
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length:   |
| 2.625 inches single mounting facility single center group   |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 3.750 inches single mounting facility single center group   |
| Frequency Rating:   |
| 60.0 hertz single component   |
| Input-output Phase Relationship:  |
| Single phase to single phase single component   |
| Body Length:  |
| 4.500 inches  |
| Body Width:   |
| 3.625 inches  |
| Body Height:  |
| 4.125 inches  |
| Inclosure Type:   |
| Open  |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Flange and unthreaded hole single group   |
| Winding Function And Quantity:  |
| 1 primary and 1 secondary single component  |
| Winding Operating Current:  |
| 30.0 amperes ac single component single secondary   |
| Winding Operating Voltage:  |
| $5.00~{\rm ac}$ volts $$ and $6.00~{\rm ac}$ volts $$ and $7.00~{\rm ac}$ volts $$ and $8.00~{\rm ac}$ volts $$ single component single secondary |
| Terminal Type And Quantity:   |
| 2 wire lead and 5 threaded stud   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A058b0  |
|   |