NSN 5950-00-518-4146

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-518-4146

_								
D		lia	hi	liŧv,	Ind	lica	ıŧα	r.
	C	на	v	HLV	IIIU	1160	ıv	ι.

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.625 inches single mounting facility single center group2.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.125 inches single mounting facility single center group2.125 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component or 50.0 hertz single component or 60.0 hertz single component60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Body Length:

3.625 inches 3.625 inches

Body Width:

3.062 inches 3.062 inches

Body Height:

4.875 inches 4.875 inches

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 3 secondary single component3 secondary single component

Thread Size:

0.164 inches single group 0.164 inches single group

Winding Operating Current:

70.0 milliamperes ac single component 3rd secondary

Winding Operating Voltage:

6.30 ac volts single component 2nd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0