# NSN 5950-00-518-4146

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-518-4146

_								
D		lia	hi	liŧv,	Ind	lica	ıŧα	r.
	<b>C</b>	на	v	HLV	IIIU	1160	ıv	ι.

Not establishednot established

#### **Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.625 inches single mounting facility single center group2.625 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.125 inches single mounting facility single center group2.125 inches single mounting facility single center group

#### Frequency Rating:

50.0 hertz single component or 50.0 hertz single component or 60.0 hertz single component60.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

#### **Body Length:**

3.625 inches 3.625 inches

#### **Body Width:**

3.062 inches 3.062 inches

#### **Body Height:**

4.875 inches 4.875 inches

#### **Inclosure Type:**

Hermetically sealedhermetically sealed

## **Mounting Facility Quantity:**

4 single group4 single group

# **Mounting Method:**

Threaded stud single groupthreaded stud single group

#### Winding Function And Quantity:

1 primary single component and 1 primary single component and 3 secondary single component3 secondary single component

#### **Thread Size:**

0.164 inches single group 0.164 inches single group

## **Winding Operating Current:**

70.0 milliamperes ac single component 3rd secondary

#### **Winding Operating Voltage:**

6.30 ac volts single component 2nd secondary

# **Thread Series Designator:**

Unc single group

## **Terminal Type And Quantity:**

10 solder stud

# Shelf Life:

N/a

#### **Unit Of Measure:**

--

## Demilitarization:

No

#### Fiig:

A058b0