NSN 5950-00-518-4390

Saturable Reactor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-518-4390

| Reliability Indicator: |
|---|
| Not established |
| Overall Length: |
| 3.000 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.650 inches single mounting facility single center group |
| Overall Height: |
| 2.000 inches |
| Overall Width: |
| 1.500 inches |
| Frequency Rating: |
| 400.0 hertz single component |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 8 single group |
| Mounting Method: |
| Threaded hole single group |
| Winding Function And Quantity: |
| 2 primary and 1 control single component |
| Saturation Current Rating: |
| 0.5 milliamperes |
| Thready Qty Per Inch (tpi): |
| 40 single group |
| Thread Size: |
| 0.112 inches single group |
| Dc Resistance Rating In Ohms: |
| 1000.000 single component single control |
| Winding Operating Voltage: |
| 70.00 ac volts single component all primary |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 9 solder stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A058b0 |