

View Online at <https://aerobasegroup.com/nsn/5950-00-518-4457>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component and 1.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.000 inches

Body Width:

2.875 inches

Body Height:

3.750 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

75.0 milliamperes ac single component 2nd secondary

Winding Operating Voltage:

580.00 ac volts single component 2nd secondary 6.50 ac volts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 standoff, solder lug

Reference Number Differentiating Characteristics:

As differentiated by pacs adaq adat adau

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0