

View Online at <https://aerobasegroup.com/nsn/5950-00-518-7522>

Reliability Indicator:

Not establishednot establishednot established

Overall Length:

5.312 inches 5.312 inches 5.312 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.375 inches single mounting facility single center group4.375 inches single mounting facility single center group4.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group2.500 inches single mounting facility single center group2.500 inches single mounting facility single center group

Overall Height:

5.250 inches 5.250 inches 5.250 inches

Overall Width:

4.250 inches 4.250 inches 4.250 inches

Mounting Slot Width:

0.196 inches single group0.196 inches single group0.196 inches single group

Frequency Rating:

50.0 hertz single component and 50.0 hertz single component and 50.0 hertz single component and 500.0 hertz single component500.0 hertz single component500.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single componentsingle phase to single phase single component

Maximum Transformer Power Rating:

0.250 volt-ampere single component0.250 volt-ampere single component0.250 volt-ampere single component

Winding Shielding Method:

Internal shield grounded to core single componentinternal shield grounded to core single componentinternal shield grounded to core single component

Inclosure Type:

Openopenopen

Mounting Facility Quantity:

4 single group4 single group4 single group

Mounting Method:

Flange single group and flange single group and flange single group and slot single groupslot single groupslot single group

Winding Function And Quantity:

2 primary single component and 2 primary single component and 2 primary single component and 2 secondary single component2 secondary single component2 secondary single component

Winding Operating Current:

2.2 amperes ac single component all secondary

Winding Operating Voltage:

104.00 ac volts single component all secondary or 104.00 ac volts single component all secondary or 110.00 ac volts single component all secondary or 110.00 ac volts single component all secondary or 120.00 ac volts single component all secondary120.00 ac volts single component all secondary

Terminal Type And Quantity:

16 threaded stud

Shelf Life:

Fig:

A058b0