

View Online at <https://aerobasegroup.com/nsn/5950-00-519-4541>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.625 inches single mounting facility single center group

Mounting Slot Width:

0.160 inches single group

Frequency Rating:

380.0 hertz and 1.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

3.000 inches

Body Width:

2.594 inches

Body Height:

2.562 inches

Maximum Operating Temp:

85.0 degrees celsius

Inclosure Type:

Open

Mounting Method:

Flange and slot single group

Winding Function And Quantity:

1 primary and 4 secondary single component

Winding Operating Current:

11.0 amperes ac single component 3rd secondary

Winding Operating Voltage:

6.40 ac volts single component 4th secondary

Unpackaged Unit Weight (non-core):

1.000 pounds

Terminal Type And Quantity:

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0